

Full Containment Fill Station Information

Class 2—meets/exceeds NFPA standards

FS-5002-2-S

Made
in
U.S.A.

- The Max-Air P/N FS-5002-2-S (stationary) is a two position full containment fill station. **Shown with optional four bottle control panel.*
- The fill station is designed for the connection of a four bank air storage (cascade) cylinders of up to but not greater than 6000 psi. The tilt-out cylinder tray accommodates two S.C.B.A. or SCUBA breathing air cylinders simultaneously or individually for the purpose of safely filling cylinders while preventing injury or death should a rupture occur.
- The fill station will not function unless the tray is in the closed position and the locking handle is up and the lock pin is engaged.
- The gauge panel is equipped with a pressure gauge for each storage cylinder (4), valves for flow control of the stored air, allowing to cascade easily from the panel.
- A self bleeding, pressure regulator 0~6000 psi with inlet and outlet pressure gauges and safety valve.
- The regulator allows you select the filling pressure to the SCUBA/SCBA cylinder.
- The fill gauges and fill valves let you select each bottle for filling or both at the same time; includes two each SCBA, CGA-347 or SCUBA fill valve with bleed.
- This unit may be fitted with a remote fill connection-**optional**.
- The interior of the fill tray is lined with high density polyethylene to protect the cylinders from abrasion when inserting and removing them.
- Each fill hose is equipped with a CGA hand wheel nut and nipple and are rated for 6000 psi operating pressure.
- Each fill position is supplied with a riser for use with cylinders that are shorter in length.
- The interior dimensions allow for the filling of taller SCUBA bottles. A SCUBA fill adapter is available for purchase.
- The heavy duty pivot mechanism has been designed for ease of opening and closing, durability and low maintenance.
- Up to 90 degrees of tilt can be achieved. If more or less tilt is required, custom adjustments may be made by the factory at the time of purchase.
- The unit has been powder coated for durability.
- Measures 30½"W x 25"D x 62"T
- Weight 575 lbs. (with 4 bottle control panel)

**Shown with optional 4 bottle control panel*

